

CEMACH Sifter Machine cGMP

Salient Features:

- Available in different models
- Noiseless, Maintenance free & high speed machine
- Portable and compact
- All contact parts and screen of SS 304 AISI stainless steel material
- SS 316 quality contact parts optional
- Electric power consumption is very less compared to reciprocating vibratory system
- Standard machine are with TEFC motor explosion proof / flame proof motor material
- Easy dismantling and cleaning facility for contact parts
- Double & Triple deck screens with outlet and hopper for bottom deck available on request



Also available
with 12" Lab Model

Technical Specifications :

Model	CMSM 20"	CMSM 30"	CMSM 36"
Screens	SS 304 (SS 316 Optional)	SS 304 (SS 316 Optional)	SS 304 (SS 316 Optional)
Screen Dia.	500 mm	750 mm	914 mm
Capacity/Hour *	20 to 200 Kgs.	30 to 300 Kgs.	30 to 325 Kgs.
Charging height	1200 ± 5 mm without Lid	900 ± 5 mm without Lid	900 ± 5 mm without Lid
	1430 ± 5 mm with Lid	1220 ± 5 mm with Lid	1220 ± 5 mm with Lid
Discharging height	720 ± 5 mm	735 ± 5 mm	735 ± 5 mm
Electric Motor	0.25 HP / 1440 RPM / 3 Ph	0.5 HP / 1440 RPM / 3 Ph	0.5 HP / 1440 RPM / 3 Ph

* Depending upon the characteristic of material and sieve & size.

NOTE : DUE TO CONTINUOUS IMPROVEMENTS IN THE MACHINERIES, SPECIFICATION OF THE MACHINERIES IS SUBJECT TO CHANGE WITHOUT ANY PRIOR NOTICE.